



Note - N.E. Corner set by prorating record distance east from $\frac{1}{4}$ Corner 25-26 and taking $\frac{1}{4}$ of the falling of adve east random line.

This map has been examined for conformance with the requirements of Chapter 15 of Division 3 of the Business and Professions Code this ---- day of ----- 1960.

----- COUNTY SURVEYOR -----

No. 501
Filed for record this 22nd day of September 1960 at 9:15 Am. in Book 2 of Maps at Page 46 at the request of A.H. Trail.

Geo. C. Delaney
COUNTY RECORDER, MONO COUNTY, CALIF.

RECORD OF SURVEY MAP

Bearings are based on the U.S.G.L.O. record bearing of N 89° 37' W of the south line of Section 25.

Being a map of a survey of the east $\frac{1}{2}$ of the SE $\frac{1}{4}$ of Section 26 and the West $\frac{1}{2}$ of the SW $\frac{1}{4}$ of Section 25 T4S R. 29 E. M.D.B. & M. made by J.H. Creed at the request of A.H. Trail.

This map correctly represents a survey made by me in conformance with the requirements of Chapter 15 of Division 3 of the Business and Professions Code.

J. H. Creed
RCE. 5521

Scale 1" = 200'

Record of Survey Map Book 2 Page 18 of Maps

Record Bearing N 0° 17' 02" W Meas. Bearing N 0° 07' 40" 1319.31 Rec. and Meas.

Set 3/4" pipe 1/4 Cor 25-26
Set 3/4" pipe 1/4 Cor 25-26

S 0° 22' 40" E 2640.00 Rec. and Meas.

S 0° 20' E 2614.00 Calc.

Set US G.L.O. Cor. Sec. 25-26
std. disc in pipe 1/4 Cor 25-26
dated 1923

N 89° 37' W 1319.67 Rec. and Meas.

Set 3/4" iron
1/4 Cor 25-26

1319.67
U.S.G.L.O. Record

Set US G.L.O. Cor. Sec. 25-26
std. disc in pipe 1/4 Cor 25-26
dated 1923